

CleanStrip ESD™ High Performance Floor Stripper

Restore ESD Properties of Old ESD Flooring

Your ESD flooring is not just any flooring product, but a functioning, technical component of your static-sensitive work environment. Using the wrong maintenance products on your floor can render it ineffective. Protect your investment by using ProtectOhm ESD™, specifically designed for use in maintenance programs whose goal is to reduce static electricity build-up and increase the conductivity of surfaces in areas where sensitive electronic components are being used or manufactured.

Residues from detergents, dirt, and floor finishes can quickly reduce the performance of any ESD Flooring. CleanStrip ESD™ is designed to effectively dissolve and remove these residues to keep your floor performing at its peak. It is formulated from top quality water-miscible solvents and contains less than 1% solids at concentration, so it leaves no residue. Old build-up can be easily removed using CleanStrip ESD™ and an auto-scrubber, using a standard stripping pad.

Use

Dilute 16 ounces of Eliminator (1:8) for routine stripping (1-10 coats), 32 ounces (1:4) for medium build-up (11-15 coats), 64 ounces (1:2) for heavy build up (15-25 coats) or 128 ounces (1:1) for severe build-up (25+ coats) per gallon of **COLD** water only.

Apply stripping solution with a mop, and let it stand for five minutes. Removing heavy finish build-up may require scrubbing with a 175-300 Rpm buffering machine equipped with a black stripping pad.

Remove the dissolved finish and solution with a wet vacuum. Any residual dissolved floor finish not removed by vacuuming should be removed by light rinsing or damp mopping.

Allow the floor to dry thoroughly before applying any new finish such as StaticStop's DuraShield ESD™ floor finish.

CleanStrip ESD™ is not recommended for use on Asphalt Tile or older Linoleum Tiles as it may remove the dye particularly from dark colored tiles.



StaticStop

a division of SelecTech, Inc.
33 Wales Ave, Suite F.
Avon, MA 02322

877-738-4537

www.staticstop.com

CleanStrip ESD™ High Performance Floor Stripper

Restore ESD Properties of Old ESD Flooring

SPECIFICATIONS		SAFETY INFORMATION
Active Ingredients	Water miscible solvents, amine complexes, alcohol ethoxylates	Health 2 Flammability 0 Reactivity 0 Personal Protection B
pH	12.8 - 13.2	CAUTION: This product contains a strong alkaline ingredient.
Free Ammonia	None	If ingested, give vinegar, juice of lemon, grapefruit, or orange freely . Do NOT induce vomiting. Get immediate medical attention.
Free Alkali	0.5%	If contact with skin or eyes occurs, flush with large volumes of water. Get immediate medical attention.
Free Acid	None	Contains 2-Butoxy Ethanol CAS #111-76-2, and 2-Amino Ethanol CAS #141-43-5.
Phosphates	None	For detailed information, consult MSDS sheet.
Abrasives	None	
Color	Light Yellow	
Odor	Moderate	
Solubility in Water	100%	
Freeze/Thaw Stability	3 cycles	
Shelf Life	Min. 1 year (30°F - 125°F.)	
Flash Point Above	200° F.	
Weight Per Gallon	8.2 lbs	
Biodegradable	Yes	
Soil Suspension	Excellent	



StaticStop

a division of SelecTech, Inc.
33 Wales Ave, Suite F.
Avon, MA 02322

877-738-4537

www.staticstop.com