

DuraBuff ESD™ Floor Gloss Maintainer

Easily Restore Gloss AND ESD Properties with Routine Maintenance

Your ESD flooring is not just any flooring product, but a functioning, technical component of your static-sensitive work environment. Using the wrong maintenance products on your floor can render it ineffective. Protect your investment by using ProtectOhm ESD™, specifically designed for use in maintenance programs whose goal is to reduce static electricity build-up and increase the conductivity of surfaces in areas where sensitive electronic components are being used or manufactured.

This innovative spray buff is formulated as a companion product for DuraShield ESD. An integral component of the conductive maintenance program, DuraBuff ESD™ is designed to extend the static dissipating qualities of DuraShield ESD™, as well as restore the gloss and enhance the appearance of conductive flooring surfaces. Its inherent static dissipating properties make DuraBuff ESD™ ideal for application in computer rooms, electronic assembly areas, telephone substations, and any other area where positive elimination of static electricity is a prime consideration. Incorporation of DuraBuff ESD™ into an static-control flooring maintenance program will extend the period of time between stripping and recoating procedures and result in saving labor and money.

Use

Remove loose dirt and soil by sweeping or vacuuming. For best results, the area to be buffed should be damp mopped with ProtectOhm ESD™ Floor Cleaner. Using a soft or medium pad, spray DuraBuff ESD™ ahead of the buffing machine, working small areas at a time.

DuraBuff ESD™ may also be diluted 32 ounces per gallon of water (1:4) for use as a mop-on restorer. Dilute the DuraBuff ESD™ in a mop bucket with cold water. Damp mop the area using a lint free cotton or combination cotton and synthetic mop. Allow the floor to dry thoroughly then burnish with a soft pad. Wash and rinse buffing pads after each application.

For optimum results, do not apply under high humidity conditions.



a division of SelecTech, Inc.
33 Wales Ave, Suite F.
Avon, MA 02322

877-738-4537

www.staticstop.com

DuraBuff ESD™ Floor Gloss Maintainer

Easily Restore Gloss AND ESD Properties with Routine Maintenance

SPECIFICATIONS		SAFETY INFORMATION	
Nonvolatile Solids	8 +/- 0.5%	Health	1
Total Active	12%	Flammability	0
Resistivity-ASTM D257	<10 ⁸ Ohms ² Max/Cm ² @ 40% Relative Humidity	Reactivity	0
pH	8.0 – 8.8	Personal Protection	B
Gloss 60° - Buffed	85	This material is not a hazardous mixture as defined in 29 CFR 1919, 1200 and M.G.L. c. 111F.	
Color	Translucent White	Safety glasses and gloves should be worn during application and handling.	
Weight Per Gallon	7.5-8.5	If ingested, drink milk, water, or fruit juice and induce vomiting with oil of ipecac. In the event of eye contact, flush area with water for 15 minutes.	
Slip Resistance (ASTM)	0.52 minimum	Contact a Physician.	
Stability	1 year minimum at room temperature	For detailed information, consult MSDS sheet.	
Freeze/Thaw Stability	3 cycles minimum		
Drying Time	30 minutes		
Water Resistance	Good		
Gallon Coverage (Feet ²)	2000 - 3500 ft ²		



a division of SelecTech, Inc.
33 Wales Ave, Suite F.
Avon, MA 02322

877-738-4537

www.staticstop.com